



3728 \$

EDELL, SHAPIRO & FINNAN, LLC
1901 Research Boulevard
Suite 400
Rockville, Maryland 20850-3164
(301) 424-3640

RECEIVED
APR 10 2003
TECHNOLOGY CENTER R3700

In re the PATENT application of

Paul Andrew Kelly, et al.

Serial No.: 09/987,238

Group Art: 3728

Filed: November 14, 2001

Examiner: John T. Kavanaugh

For: STUDED FOOTWEAR

COMMISSIONER FOR PATENTS
Washington, D. C. 20231

TRANSMITTAL LETTER

Sir:

Transmitted herewith for filing in the above-identified application are an Amendment (8 pages); Supplemental Information Disclosure Statement; Information Disclosure Citation Form (1 Page); Copy of 1 foreign patent; and Check No.6730 in payment of IDS fee.

SMALL ENTITY

CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NO. PREV. PD. FOR	PRESENT EXTRA	ADD'L FEE
TOTAL 30 - 30 = 0	0 x 9 =	\$ 0.00	
INDEP 3 - 3 = 0	0 x 42 =	\$ 0.00	
TOTAL FEE =			\$ 0.00


The Commissioner is hereby authorized to charge payment of any additional fees required for the above-identified application or credit any overpayment to Deposit Account No. 05-0460.

Respectfully submitted,

A handwritten signature in black ink, appearing to read 'Ira C. Edell', written over a horizontal line.

Ira C. Edell
Registration No. 24,119

Hand Delivered: 4/4/2003



Attorney Docket No. 1332.0191C

Handwritten notes:
#66
Electron
as mult
N. H. H. H.
4-15-03

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

5 In re the PATENT application of
Paul Andrew Kelly, et al.

Serial No.: 09/987,238

Group Art Unit: 3728

10 Filed: November 14, 2001

Examiner John T. Kavanaugh

For: Studded Footwear

AMENDMENT

RECEIVED

APR 10 2003

TECHNOLOGY CENTER R3700

15 Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

20 Sir:

In response to the Office Action dated March 4, 2003, please amend
the application as indicated below.

IN THE CLAIMS:

25 Please amend the claims to read as follows:

- al*
- 1 1. (Amended). A combination of a shoe stud and receptacle wherein
 - 2 the shoe stud includes a ground-engaging part and the two components are
 - 3 adapted to be secured together by a multi-start threaded connection
 - 4 comprising a screw-threaded spigot on one of the two components adapted
 - 5 to be inserted with rotation into a screw-threaded socket on the other
 - 6 component, and a locking means for the components arranged to become
 - 7 inter-engaged at least when the spigot is fully inserted into the socket to
 - 8 resist unscrewing of the assembly, characterized in that the stud and
 - 9 receptacle have means to determine the initial position of the stud relative